## **NETGEAR®**

### **SOHO Fast Ethernet Switches**

Data Sheet

300 Series






## **Expanding Wired Connectivity for SOHO Networks**

NETGEAR 300 Series Fast Ethernet Unmanaged Switches provide easy, reliable, and affordable network connectivity for home and small offices. With these unmanaged plug-and-play switches, you can expand your network connections to multiple devices instantly.

- Auto-MDI/MDIX eliminates the need for crossover cables
- LED indicators for ease of use
- Energy-efficient technology for power savings
- Fanless design for silent operation
- Auto-negotiation for automatic connection at the highest common speed between switch and an end device
- Non-blocking switching architecture for maximum throughput at wire speed

- · Plug-and-play; no setup required
- · Durable and rugged metal case
- Desktop or wall-mountable
- · Ideal for small office and home networks
- Standards-based technology ensures interoperability with any standards-based devices in the existing network



# **NETGEAR®**

## **SOHO Fast Ethernet Switches**

Data Sheet

300 Series

FEATURES	FS305	FS308
10/100Mbps PORTS	5	8
ENCLOSURE	Metal	Metal
CONNECTOR TYPE	Plastic	Plastic
PERFORMANCE: Bandwidth Buffer Memory Jumbo Frames Forwarding Rate (using 64-byte packets) - 100Mbps Port Latency (using 64-byte packets) - 100Mbps Port (average) MAC Address Table Size	1Gbps 48 KB 2,048 bytes 144,800 pps < 4.5 μsec	1.6Gbps 96 KB 2,048 bytes 144,800 pps < 4.5 µsec
ENERGY EFFICIENCY: Energy Efficient Ethernet (IEEE 802.3az) Auto Power Down Short Cable Detection DC Input Power Consumption (Max and Standby) Power On/Off Switch Heat Dissipation (Max and Standby) BTU/Hr	Yes Yes No 5V / 0.7A 1.8W / 0.7W No 6.16 BTU / 2.39 BTU	Yes Yes No 5V / 0.7A 2.3W / 1.2W No 7.87 BTU / 4.10 BTU
PORT LEDS	Power, Link / Activity	Power, Link / Activity
PHYSICAL SPECIFICATIONS: Width x Depth x Height Weight	101 x 94 x 29 mm 0.24 kg	158 x 101 x 29 mm 0.36 kg
ENVIRONMENT: Operating Temperature Storage Temperature Operating Humidity Storage Humidity	0 ~ 40°C -20 ~ 70°C 90% maximum relative humidity, non-condensing 5% to 95% relative humidity	

### **STANDARDS**

- 802.3u 100BASE-TX Fast Ethernet
- 802.3i 10BASE-T Ethernet IEEE
- 802.3x Flow Control
- 802.3 CSMA/CD
- 802.3az Energy Efficient Ethernet

### WARRANTY\*

- All except China/India: 3-year warranty
- China/India: 1-year warranty





F

Actual SKU availability may vary per region. Please check the local website for product availability.

NETGEAR, the NETGEAR logo are trademarks and/or registered trademarks of NETGEAR, Inc. and/or its subsidiaries in the United States and/or other countries. Other brand names mentioned herein are for identification purposes only and may be trademarks of their respective holder(s). Information is subject to change without notice.

© 2016 NETGEAR, Inc. All rights reserved.

<sup>\*</sup> This product comes with a limited warranty that is valid only if purchased from a NETGEAR authorized reseller, and modifications to product may void the warranty; see http://www.netgear.com/about/warranty/ for details. 24/7 basic technical support provided for 90 days from purchase date when purchased from a NETGEAR authorized reseller.

<sup>†</sup> NETGEAR #1 in US Market Share according to NPD data for Unmanaged and Web/Smart Switches, April 2015.