



TECHNOLOGIE OPTIC.CA INC.

100 Gigabit QSFP28 Passive Direct-Attach Copper Cable

ACC761-11100S · 100GBASE-CR4 · 1m · QSFP28-to-QSFP28 · 30 AWG twinax · Optic.ca Q28-CU1M-NT-OC

The Optic.ca ACC761-11100S is a 100 Gigabit QSFP28 passive direct-attach copper (DAC) cable assembly for short-reach, high-density 100G interconnect within a rack. It carries four independent 25.78 Gb/s lanes (103.1 Gb/s aggregate) over a 1 m, 30 AWG twinaxial cable with 100 Ω differential impedance and QSFP28 connectors at both ends, built to align with the applicable QSFP28 SFF multi-source agreements and IEEE 802.3bj. As a passive assembly it contains no active signal-conditioning or optical components, providing the lowest-latency, lowest-power 100G connection for top-of-rack switch-to-switch links. Each assembly is individually serialized, factory-coded for host-platform compatibility, and validated prior to shipment, and is backed by the Optic.ca lifetime warranty.

Key Features

- Compliant with the QSFP28 SFF-8665 and SFF-8679 specifications; supports IEEE 802.3bj 100GBASE-CR4
- Four independent full-duplex lanes; 25.78125 Gb/s per lane (103.1 Gb/s aggregate)
- 1 m, 30 AWG twinaxial copper cable; 100 Ω differential impedance
- AC-coupled passive construction — no active or optical components in the signal path
- All-metal connector housings for superior EMI shielding
- Factory-coded EEPROM for host-platform compatibility
- Commercial operating temperature range: -5 °C to +70 °C
- TAA compliant (Country of Origin: Taiwan); RoHS and REACH compliant
- Certified compatible with NETGEAR® switching platforms

Target Applications

- 100 Gigabit Ethernet top-of-rack interconnect
- Switch-to-switch links within a rack
- High-density data-center and HPC fabrics
- InfiniBand QDR/EDR clusters

Ordering Information

Part Number	Description
ACC761-11100S	100GBASE-CR4 QSFP28 passive DAC, 1 m, 30 AWG, 100 Ω twinax, QSFP28-to-QSFP28; NETGEAR® Certified Compatible

Standards Compliance

The ACC761-11100S is designed and manufactured to comply with the applicable standards listed below. These statements indicate conformance to the referenced specifications; they do not constitute third-party certification, agency listing, registration, or regulatory approval unless explicitly stated otherwise.

Standard / Program	Detail
Interface & MSA	

Standard / Program	Detail
QSFP28 SFF-8665	QSFP28 form factor and high-speed interface
QSFP28 SFF-8679	QSFP28 hardware and electrical specification
IEEE 802.3bj	100GBASE-CR4 copper PMD
High-speed electrical	AC-coupled, 100 Ω differential signal paths
Environmental & Trade	
EU RoHS (2011/65/EU, incl. 2015/863)	Compliant
REACH (EC 1907/2006)	Compliant
Trade Agreements Act (TAA)	Compliant — Country of Origin: Taiwan

Note: EMC and product safety for a cable assembly are determined at the host-equipment level. The assembly is designed to conform to the listed limits and requirements when installed in compliant host equipment.

NETGEAR® Certified Compatible — validated for interoperability with NETGEAR switching platforms. NETGEAR® is a registered trademark of NETGEAR, Inc. This Technologie Optic.ca Inc. product is certified compatible under NETGEAR's certification program; it is not a NETGEAR-branded product.

General Specifications

Parameter	Value
Number of lanes	4 (Tx and Rx)
Channel data rate	25.78125 Gb/s per lane (103.1 Gb/s aggregate)
Operating case temperature	–5 °C to +70 °C
Storage temperature	–40 °C to +85 °C
Supply voltage (management interface)	3.3 V nominal
Host electrical interface	QSFP28 38-pin edge connector
Management interface	2-wire serial (I ² C)

High-Speed Electrical Characteristics

Parameter	Symbol	Min.	Max.	Units	Conditions
Differential impedance	R _n (p-p)	90	110	Ω	—
Insertion loss	SDD21	—	22.48	dB	at 12.89 GHz
Common-mode return loss	SCC11	2	—	dB	0.2–19 GHz
Channel operating margin	COM	3	—	dB	—

Differential return loss (SDD11, SDD22) conforms to the applicable IEEE 802.3 return-loss limits over 0.05–19 GHz.

Cable Construction

Parameter	Value
Cable type	Passive twinaxial copper
Conductor gauge	30 AWG
Differential impedance	100 Ω nominal (90–110 Ω)
Cable length	1 m
Connectors	QSFP28 at both ends

Parameter	Value
Signal coupling	AC-coupled
Shielding	All-metal connector housings for EMI suppression

Pin Assignment — QSFP28 Connector

PIN	Symbol	Description
1	GND	Ground
2	Tx2n	Transmitter inverted data input
3	Tx2p	Transmitter non-inverted data input
4	GND	Ground
5	Tx4n	Transmitter inverted data input
6	Tx4p	Transmitter non-inverted data input
7	GND	Ground
8	ModSelL	Module select
9	ResetL	Module reset
10	VccRx	+3.3 V receiver power supply
11	SCL	2-wire serial interface clock
12	SDA	2-wire serial interface data
13	GND	Ground
14	Rx3p	Receiver non-inverted data output
15	Rx3n	Receiver inverted data output
16	GND	Ground
17	Rx1p	Receiver non-inverted data output
18	Rx1n	Receiver inverted data output
19	GND	Ground
20	GND	Ground
21	Rx2n	Receiver inverted data output
22	Rx2p	Receiver non-inverted data output
23	GND	Ground
24	Rx4n	Receiver inverted data output
25	Rx4p	Receiver non-inverted data output
26	GND	Ground
27	ModPrsL	Module present
28	IntL	Interrupt
29	VccTx	+3.3 V transmitter power supply
30	Vcc1	+3.3 V power supply
31	LPMODE	Low power mode
32	GND	Ground
33	Tx3p	Transmitter non-inverted data input
34	Tx3n	Transmitter inverted data input

PIN	Symbol	Description
35	GND	Ground
36	Tx1p	Transmitter non-inverted data input
37	Tx1n	Transmitter inverted data input
38	GND	Ground

Handling

- Hold the connector by its sides when inserting it into the switch port.
- Do not handle the assembly by the cable.
- Do not over-bend the cable behind the connector.
- Do not twist or kink the cable.
- Do not flex the cable up and down behind the connector.

This document is provided by Technologie Optic.ca Inc. for informational purposes only and is subject to change without notice. While reasonable care has been taken in its preparation, Optic.ca makes no warranty, express or implied, as to its accuracy or completeness, and assumes no liability arising from its use. Specifications represent typical performance over the stated operating conditions and do not constitute a guarantee of suitability for a particular application; the customer is responsible for validating suitability for their deployment. NETGEAR® is a registered trademark of NETGEAR, Inc. This is a Technologie Optic.ca Inc. product, certified compatible under NETGEAR's certification program; it is not a NETGEAR-branded product. Country-of-origin and Trade Agreements Act status are representations as of this revision, supported by supplier documentation on file. © Technologie Optic.ca Inc. All rights reserved.